



CUP WALL 6 alu pol/glow


CWA80-0

With the wall luminaire **CUP WALL 6**, the light is emitted both upwards and downwards. Through the OPTIC 6, the light is deglared and directed in such a way to atmospherically illuminate the wall and room. The OPTIC 6 is interchangeable and available in various colours.

The CHOICE configurator allows the luminaire to be individually configured.

Design: Tobias Grau

CUP WALL 6 alu pol/glow CWA80-0



TECHNICAL SPECIFICATIONS

Lamp holder	LED
Mounting method	wall-mounted (surface)
Light emission	direct/indirect
Light distribution	asymmetric
Luminaire luminous flux	220 lm
Colour temperature	2700 K
Colour rendering index (CRI)	> 90
White impression	warm white
Rated voltage (range)	220-240 V
Power frequency	50 / 60 Hz
Power consumption (maximum)	12 W
Surface	polished
Housing material	aluminium
Type of lamp control gear	Driver
Ballast included	Yes
Protection class	I
Connection cable (number of cores)	3
Number of lampheads	2
Lampshade material	plastic
Energy efficiency	A - A++
Dimmable	Yes
Type of Dimmer	phase rotary dimmer
Length	150 mm
Width	60 mm
Height	65 mm
Head adjustable	No